


IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Switches for appliances
Name and address of the applicant	Everel Group S.p.A. Via Cavour, 9 37067 Valeggio sul Mincio (VR) Italy
Name and address of the manufacturer	Everel Group S.p.A. Via Cavour, 9 37067 Valeggio sul Mincio (VR) Italy
Name and address of the factory	<input type="checkbox"/> Additional information on page 2 Everel Group S.p.A. Via Cavour, 9 37067 Valeggio sul Mincio (VR) Italy
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	Switches for class II appliances; overvoltage category II; rated impulse withstand voltage 2,5 kV; PTI250. (see also pages from 5 to 8 of Test Report No. MI19-0046338-01 and/or Additional Sheet)
Trademark (if any)	 ED
Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	Series DY (see also Additional Sheet)
Additional information (if necessary may also be reported on page 2)	<input type="checkbox"/> Additional information on page 2
A sample of the product was tested and found to be in conformity with	IEC 61058-1-1:2016, IEC 61058-1:2016 National differences: EU Group Differences
As shown in the Test Report Ref. No. which forms part of this Certificate	MI19-0046338-01, MI19-0046338-01/1, MI19-0046338-01/2 and MI19-0046338-01/3

This CB Test Certificate is issued by the National Certification Body

IMQ S.p.A.
Via Quintiliano 43, IT-20138 Milano, Italy

Description of the switches for appliances series DY

Type reference ⁽¹⁾	Rated current, rated voltage and nature of supply	Code	Disconnection	Rated operating cycles	Rated ambient temperature						
1-DY/...	6(2) A – 250 V ac	1.2 bistable	Full disconnection	1E4	T150/55						
2-DY/...		1.2 momentary action	Full disconnection								
1-DY/...		1.3 bistable	Full disconnection								
1-DY/...	16(6) A – 250 V ac	1.2 bistable	Full disconnection		1E4	T125/55					
2-DY/...		1.2 momentary action	Full disconnection								
1-DY/...		1.3 bistable	Full disconnection								
2-DY/...	12(4) A – 250 V ac	1.5 bistable	Full disconnection				1E4	T125/55			
1-DY/...		2.3 bistable	Micro disconnection								
2-DY/...		2.7 bistable	Micro disconnection								
1-DY/...	6 A – 400 V ac	1.2 bistable	Full disconnection						1E4	T125/55	
2-DY/...		1.2 momentary action	Full disconnection								
1-DY/...		1.3 bistable	Full disconnection								
1-DY/...	6(4) A – 250 V ac	1.2 bistable	Full disconnection	1E4							T125/55
2-DY/...		1.2 momentary action	Full disconnection								
1-DY/...		2.3 bistable	Micro disconnection								
2-DY/...		1.3 bistable	Full disconnection								
1-DY/...		1.5 bistable	Full disconnection								
2-DY/...		2.7 bistable	Micro disconnection								
1-DY/...	0,02 A – 24 V dc	1.2 bistable	Full disconnection		1E4	T125/55					
2-DY/...		1.2 momentary action	Full disconnection								
1-DY/...		2.3 bistable	Micro disconnection								
2-DY/...		1.3 bistable	Full disconnection								
1-DY/...		1.5 bistable	Full disconnection								
2-DY/...		2.7 bistable	Micro disconnection								
1-DY/...	10(4) A – 250 V ac	1.2 bistable	Full disconnection	5E4			T125/55				
2-DY/...		1.2 momentary action	Full disconnection								
1-DY/...		2.3 bistable	Micro disconnection								
2-DY/...		1.3 bistable	Full disconnection								
1-DY/...		1.5 bistable	Full disconnection								
2-DY/...		2.7 bistable	Micro disconnection								

(1) – The description of the type reference is given on page 2

Description of the type reference of the switches for appliances series DY

- DY /

